

## C7815WIP HD WIF Network Camera



Product Name: C7815WIP HD WIF Network Camera

Model No.: C7815WIP

### Product Abstract:

C7815WIP HD WIF Network Camera, 8-level user authority management, built in watchdog, can auto test chipset and software.



### Product Description

Model : C7815WIP		
Features	System security	8-level user authority management, built in watchdog, can auto test chipset and software.
	Built-in dynamic IP domain system (Free)	No need domain name, support dynamic IP.
	Mobileview platform	No need install software, multi-channel mobile view, support mobile view alarm snapshot.
	Plug & Play	Plug & Play technology applied.99% penetration rate. Only three steps to view image.
	UID Technology	Unique scan UID to add camera, easy to operate, and highly confidential.
	CMS	1、4、9、16、25、36、64、81-channel central management surveillance system, no user limitation. Centralized monitoring, remote recording, remote playback.
Core	O.S	Built in Linux
	Control protocol	ONVIF protocol,high interoperability
	Processor	Hi3518E processor,built in ARM9 @Max. 440MHz and High-speed video co-processor
Video	Compression format	H.264 Baseline Profile@H.264 Main Profile@MJPEG/JPEG Baseline
	resolution/frame rate	720p/VGA/QVGA 30fps/25fps
	Image adjustment	Brightness, Contrast, Saturation are adjustable
	Sensor	1/4 720p Progressive CMOS sensor
	Minimum illumination	1.0 Lux / F1.2

	CMOS	support AWB,AGC,BLC
	Sensor size	3.84mm×2.16mm
	Video coding	Multi stream: 720P@30fps+VGA@30fps+QVGA@30fps+720P @1fsJPEG capture
	Bit Rate	CBR/VBR,output range: 32kbps~40Mbps
	Lens/viewing angle	3.6mm/56.14°
Night Vision	Night vision	Dual IR-CUT Filter auto switch, 30pcs 850nmΦ5mm LED,15m IR distance
Network	Socket	10/100Mb self-adaptable Ethernet slot
	Network Protocol	TCP/IP,HTTP,RTSP,TCP,UDP,SMTP,FTP,DHCP,DNS,DDNS,NTP,UPnP,,P2P ect.
	Online visitor	Support 10 online visitors viewing simultaneously
	IP address	Dynamic IP and static IP address
	WIFI	WIFI 802.11 b/g/n
	Network adaptability	can auto adjust stream and frame rate according to the bandwidth
Others	Housing material	Engineering-plastics
	Use Enviroment	both indoor and outdoor
	Power supply	DC12V±10%
	Working temperature	-20 ~ 50 °C
	RTP	Support RTP, can auto adjust time when restart after power failure.
	Accessories	Power adapter, user manual, warranty card,mounting bracket,screws.
	Motioin Detection	can setup motion detection sensitivity
	Alarm notification	E-mail snapshot, FTP upload alarm pic and video.
System Requirements	Operating System	Win98 SE/ME/2000/XP/Vista/win7 IE5.0, NET4.5, firefox, chrome
Certificate	Certificates	ISO FCC CE RoHS
		Only for reference