



Feature:

- 1)Autofocus 2.8-12mm Lens
- 2)P/T/Z (4X Optical Zoom)
- 3)3G/4G SIM Card Slot
- 4)Strong double antenna 5db
- 5)SD Card Slot for local storage
- 6)4pcs Array IR LED
- 7)Plug-Play easy Setting (APP: CAMHI)
- 8) Sim card Not include,SD card not include

Lens		2.8-12mm
3G/4G	3G/4G network standard	4G FDD-LTE/TD-LTE/WCDMA/HSPA+/TD-SWCDMA/GSM/GPRS/EDGE
	Bands	B1/B3/B7/B20/B38/B39/B40/B41/B26
	Transmission Speed	LTE FDD/TDD (Cat. 4) download 150 Mbps . Upload 50 Mbps 3G HSPA+ download 21 Mbps, Upload 5.76 Mbps 3G TD-SCDMA download 2.8 Mbps, Upload 2.2 Mbps
	3G/4G Video Transmission channel	LTE B1/B3/B8/B38/B39/B40/B41 (CA not support) TD-SCDMA B34/B39 WCDMA 2100/900MHz GSM/GPRS/EDGE 900/1800MHz
	Signal Strength Detection	Support
	SMS	Support SMS sending
	SIM card slot	Support. Standard USIM card.
	SIM card lock	Support
Alarm	SMS Alarm	Support
	3G Video Call Alarm	Support
	Motion Detection Alarm	Support. 3 sensitivity levels: low, standard, high
	Alarm Platform	Support iPhone push alarm
	Alarm Video Recording	Support
	Alarm recording	Support. The video will be recorded 5 seconds before the alarm triggered time.
	Alarm Zone	Alarm Zone
	Alarm Level	Alarm Level
Record	Record File Format	AVI file format
	Record Storage	Internal TF Storage. FAT file system. Maximum 32GB
	Recording mechanism	The least recently used file will be deleted when the available storage is less than 10%.
	Manual recording	Support. User can start and stop the recording using the client application
	Record searching	Support. Search by record time and type.
	Record management	Support User can download, batch delete and one-click delete the record.
	24 hours	Support. Scheduled by week day and time. Each record can be 10, 15, 30, 60 minutes long.

	recording or scheduled recording	
	Online Record Watching	Support. User can watch the whole video or preview the key frame of the video.
Auto	Auto Exposure	Support
	Auto White Balance	Support
	Electronic shutter	Auto Exposure
Wi-Fi	Wi-Fi	WiFi 802.11g/n
	WiFi Mode	AP and STA mode. Switching comes into effect in 5 seconds
General	Day and night function	Yes
	Clock	RTC real time clock. Support NTP and remote setting.
	Voltage	12V DC
	Power	Maximum power consumption 12W minimum power consumption 5W
	Working Environment	Working Temperature -20℃~+50℃, Working humidity 10%~90%